ACS MOTION CONTROL

Smarter Motion

35+ Years of Smarter Motion



Economical Control Module (ECM) Series



- *All-in-one motion controllers with integrated drives*
- *For cost- and space-sensitive OEM machines up to 4 axes*



SPiiPlus Platform

- *Flagship EtherCAT-based motion control ecosystem*
- *For high-tech OEM machines with demanding throughput and accuracy requirements*
- *Up to 128 axes, 5 kHz max control network rate, 20 kHz servo rate*
- *Unique algorithms to enhance performance and machine uptime*

***Servo**Boost™* ***Servo**Boost Plus™* ***Learning**Boost™* ***Motion**Boost™*



Intelligent Drive Module (IDM) Series

- *DS402 EtherCAT drives for high-precision motion stages*
- *For OEM machines with demanding motion requirements*

EtherCAT Conformance tested



Common Software Tools

SPiiPlus ADK Suite

MMI Application Studio
Motion control sytem configuration, application development, and performance optimization

Controller Simulator
Develop host and controller application code rapidly without hardware

Host Application Libraries
APIs for developing high-tech OEM machine UIs

LabVIEW .NET

Smarter Motion Tools (SMT)
Define, measure, and verify motion system performance specifications

Advanced Analysis Libraries
APIs for developing advanced data/performance analysis UIs and preventive maintenance features

Host PC/PLC

Ethernet TCP/IP & UDP EtherNet/IP Modbus

PLC

Host PC/PLC

Ethernet TCP/IP & UDP EtherNet/IP Modbus

Host PC/PLC

Non-ACS Controller

EtherCAT

MOTION CONTROLLERS WITH DRIVES

ECMSA — *12-150 Vdc, 15/30 A** — 1 axis
ECMSM — *12-48 Vdc, 5/10 A* — 4 axis
ECMMA — *24-150 Vdc, 15/30 A** — 4 axis
ECMDX — *100-240, 360-440 Vac, 15/30 A* — 2 axis

MOTION CONTROLLERS

SPiiPlusSCLT/HP — *PC-Based Soft Controller*

SPiiPlusES — *Dual EtherCAT master/slave functionality*

SPiiPlusEC

EtherCAT

MOTION CONTROLLERS WITH INTEGRATED DRIVES (CONTROL MODULES)

CMNT — *85-265 Vac, 7.5/15 A* — 2 axis
CMXA — *85-265 Vac, 15/30 A* — 3 axis
CMHV — *185-250, 400-525 Vac, 15/30 A (480Vac), 20/60 A (230Vac)* — 2 axis
MP4U — *100-240 Vac, 13.3/40 A* — NanoPWM™ — 8 axis
MC4U — *8 built-in drives, 85-265 Vac, 45/90 A** — NanoPWM™ — 8 axis

EtherCAT

DRIVES

UDMLC — *12-48 Vdc, 2.5/5 A (4 axis), 5/10 A (2 axis)* — 4 axis
UDMSD — *12-48 Vdc, 2.5/5 A* — 4 axis
UDMSM — *12-48 Vdc, 5/10 A* — 4 axis
UDMNT — *12-80 Vdc, 10/20 A* — 2 axis
UDMSA — *12-150 Vdc, 15/30 A** — 1 axis
UDMMA — *24-150 Vdc, 15/30 A** — 4 axis
UDMCB, NPMPC — *12-100 Vdc, 13.3/40 A* — NanoPWM™ — 2 axis

DRIVE INTERFACES

PDICL — *Pulse/Direction command interface* — 4 axis
UDILT/HP — *+/-10 V command interface* — 4 axis

I/O & LASER CONTROL

UDMPA, NPMPM — *12-100 Vdc, 13.3/40 A* — NanoPWM™ — 2 axis
UDMPM — *85-265 Vac, 7.5/15 A* — 2 axis
UDMDX — *100-240, 360-440 Vac, 15/30 A* — 2 axis
UDMXA — *85-265 Vac, 15/30 A* — 3 axis
UDMHV — *185-250, 400-525 Vac, 15/30 A (480Vac), 20/60 A (230Vac)* — 2 axis
MP4UDC — *100-240 Vac, 13.3/40 A* — NanoPWM™ — 8 axis
MC4UDC — *85-265 Vac, 45/90 A** — NanoPWM™ — 8 axis
IOMNT — *32/32 digital (source type)*
IOMPS-ED — *32/32 digital (sink type)*
IOMPS-EA — *4/0, 0/4 analog (+/- 10V)*
LCI — *High-speed digital and analog I/O for laser and measurement device control*

DRIVES

IDMSA — *12-150 Vdc, 15/30 A** — 1 axis
IDMSM — *12-48 Vdc, 5/10 A* — 4 axis
IDMMA — *24-150 Vdc, 15/30 A** — 4 axis
IDMDX — *100-240, 360-440 Vac, 15/30 A* — 2 axis

EtherCAT Conformance tested

ACS Product Map v1.0

** Max current not available for all configurations / axes*

EtherCAT® is registered trademark and patented technology, licensed by Beckhoff Automation GmbH, Germany.